




ROTAJET DEGREASING MACHINERY

DuelJet Washer



Automatic spray + manual high pressure wash

The multi-stage spray washers offer an additional step to thoroughly rinse and dry the washed parts.

This addition ensures that the surface of the material is completely free from any remaining residue that collects into any fine lines or sits on the metal's surface causing surface stains.


Applications

- To wash motor blocks and parts
- To wash any parts at bus, truck, automobile and work machines
- At the workshop which manufacture machining parts and oiled part
- At the firms which engine reconditioning and cylinder head repairing

Features:



- Completely manufactured with stainless steel sheets and components
- Cleaning process timing
- Developed for minimum water, detergent and electric consumption
- Minimum water consumptions by closed water cycling system.
- Heated water (solution) dispensed through high-pressure jet nozzles
- Pneumatic front door movement
- High user safety with pneumatic pistons
- Gear driven rotary table
- Automatic water feeding system



ROTAJET DEGREASING MACHINERY

DuelJet Washer



Safety Interlocks

Safety interlocks are automatically engaged during the operation of the machine and are only disengaged when the cycle has come to an end and temperatures have returned to a safe level.



Intergrated control measures


We put all the measures in place to so your products are cleaned thoroughly, whilst ensuring the safety of the operator and the longevity of your machine.




Standard sizes

To account for our customers' varying needs, we have produced standardised sizes for our front loading spray washers which are perfect for the majority of degreasing applications. Find the specs below.

MODEL	DUELJET X12	DUELJET X14
Basket diameter	1200	1400
Loading height (mm)	700	700
Loading capacity (kg)	500	650
Tank capacity (Lt)	250	300
Pump Pressure (bar)	2.5	2,5
Pump quantity and Power	1 Piece x 3, Hp	2 pieces x 3 Hp
Heater (kW)	15	22,5
Electricity (V/phrse/Hz)	220-380-415/ 1-3/ 50-60	220-380-415/ 1-3/ 50-60
Process timer (min)	0-90	0-90
Working Temp(°C)	0-80	0-80
Rotary Basket	Standard	Standard
Oil Skimmer	Standard	Standard
Packing size and weight (mm)	1820-1530-2410-600kg	1920x2020x2440- 700kg



info@rotajet.co.uk
rotajetsystems.co.uk
14 Flanshaw Way, Wakefield
WF2 9LP



ROTAJET DEGREASING MACHINERY

DuelJet Washer

Optional Extras:

- Drying Unit
- Safety light barrier
- Automatic basket loading system
- Steam extraction
- PLC control and touch-screen

MODEL	DUELJET X16	DUELJET X18
Basket diameter	1600	1800
Loading height (mm)	800	900
Loading capacity (kg)	750	850
Tank capacity (Lt)	350	450
Pump Pressure (bar)	2.5	2,5
Pump quantity and Power	3 Piece x 3,Hp	3 pieces x 3 Hp
Heater (kW)	22,5	22,5
Electricity (V/phrse/Hz)	220-380-415/ 1-3/ 50-60	220-380-415/ 1-3/ 50-60
Process timer (min)	0-90	0-90
Working Temp(°C)	0-80	0-80
Rotary Basket	Standard	Standard
Oil Skimmer	Standard	Standard
Packing size and weight (mm)	2220-1930-2510-800kg	2430x2320x2640- 950kg



info@rotajet.co.uk
rotajetsystems.co.uk
14 Flanshaw Way, Wakefield
WF2 9LP

DUELJET WASHER